

केन्द्रीय विद्युत अनुसंधान संस्थान

(भारत सरकार की सोसाइटी, विद्युत मंत्रालय)

प्रो सर सी. वी. रामन रोड़, सदाशिवनगर डाक घर, पो. बा. सं. 8066, बेंगलूर - 560 080

CENTRAL POWER RESEARCH INSTITUTE

(A Govt of India Society under Min. of Power)

Prof. Sir C.V. Raman Road, Sadashivanagar P.O., P.B. No. 8066, Bangalore - 560 080, India वेबसाइट/website : http://www.cpri.in

ENERGY EFFICIENCY AND RENEWABLE ENERGY DIVISION

Phone/Tele fax: 080-23604682 email: msb@cpri.in, ered@cpri.in

CPRI/ERED/SPV/2013

07/10/2013

To,

M/s. Focusun Energy Systems, Old No. 27, New No. 30, Dr. Jaganathan Nagar, Opp. Medical College, Aerodrome Post, Coimbatore

Dear Sir,

Please find enclosed the test report for the following:

m.

1. LED based Solar Street Lighting System - 1 No.

Please acknowledge the receipt of the test report. Thank you for utilizing our services.

Corrections, if any, in the report may please be brought to our notice within 45 days from the date of issue of the report.

Kindly arrange to take back the equipment tested within 15 days, failing which the same will be disposed off.

Thanking you,

Yours Sincerely,

(M. Siddhartha Bhatt)
Additional Director

CENTRAL POWER RESEARCH INSTITUTE ENERGY EFFICIENCY AND RENEWABLE ENERGY DIVISION

Submitted By: M/s. Focusun Energy Systems

Sample ID: S2965

Date of Issue: 07/10/2013



TEST REPORT

SL. No. Particulars		Details	
01	Test report no.	CPRI/ERED/SPV/2778/2013	
02	Date	07/10/2013	
03	Client's address	M/s. Focusun Energy Systems, Old No. 27, New No. 30, Dr. Jaganathan Nagar, Opp. Medical College,	
	24	Aerodrome Post, Coimbatore	
04	Reference	Nil, Dated 01/08/2013	
05	Manufacturers address	Same as above	
06	Reference		
07	Sample tested	White LED based Solar Street Lighting System	
08	Designation		
09	Configuration		
10	Identification no.	ERED/SPV/LED/S2965/2013	
11	Serial no.	FS0127	
12	Date (s) of the test	28/08/2013 to 29/09/2013	
13	No. of samples tested	One	
14	Test in accordance with standards/specifications	MNRE Specifications 2013-2014	
15	Client's requirement	Nil	
16	Deviation (if any)	Nil	
17	Name of the witnessing persons	Nil	
18	Clients representative	Nil	
19	Other than clients representative	Nil	
20	No. of pages (including this page)	Four	
21	No. of oscillograms	Nil	
22	No. of drawings	Nil	
23	No. of graphs	Nil	
24	No. of photos	Nil	



(M. Siddhartha Bhatt)
Additional Director

NOTE:

a) This is not a certificate of compliance.

b) These test results relate only to the items tested, which are selected and submitted by the client mentioned above.

c) The data reported in this test report are valid at the time of and under the stipulated conditions of measurements.

d) Publications or reproduction of this report in any form other than by complete set of the whole report and in the language written is not permitted without consent of CPRI.

e) Correction/erasing invalidate the test report.

Test in- charge

Total No. of pages	Page No.	Report No.
4	. 1	2778

Test Engineer

CENTRAL POWER RESEARCH INSTITUTE ENERGY EFFICIENCY AND RENEWABLE ENERGY DIVISION

Submitted By: M/s. Focusun Energy Systems

Sample ID: S2965

Date of Issue: 07/10/2013



TEST RESULTS

SL. No.	Test description	Observations	Requirement as per MNRE specifications 2013-2014	Remarks
		1.0 PV MODU	JLE	
1.1	Type of module	Poly crystalline silicon	Mono or poly crystalline silicon	
1.2	Manufacturer	M/s. Udhaya Semiconductors Limited		
1.3	SL. No.	13206747	35	(RF id provided)
1.4	Module configuration	1 x 40 W	One 40 Wp module	
1.5	Open circuit voltage at STC	21.01 V DC	≥ 21.0 VDC	
1.6	Peak power at 16.4 V	41.31 Wp	≥40 Wp	See below*
1.7	PV Module efficiency	12.22 %	12.00 %	
		2.0 LAMP		
2.1	Make	M/s. Seoul		
		Semiconductors		
2.2	Model No.	SZW05A013		
2.3	No. of LED/luminaire	9 Nos.		
2.4	Light output			
	Average lux levels at 4 meter height and 4 meter periphery	Centre: 21.22 Lux Avg. Lux: 17.14 Lux	15.0 lux	
		3.0 BATTER	Y	
3.1	Make	M/s. Exide		
3.2	Serial No	3VB025056		
3.3	Type of battery	LMLA	Lead acid tubular plate /VRLA	
3.4	Capacity at C/10 discharge rate (12V)	40.0 Ah	40.0 Ah.	
3.5	% of rated capacity between battery high and low	37.05 Ah 92.62 % 50hrs.40 min	75 %	

*PV module is manufactured as per IEC61215 standards. Vide test report No.21154280.001 dated 26/07/2010 issued by TUV Rheinland.

S. J. L. bar Test in- charge

Total No. of pages Page No. Report No.
4 2 2778



CENTRAL POWER RESEARCH INSTITUTE ENERGY EFFICIENCY AND RENEWABLE ENERGY DIVISION

Submitted By: M/s. Focusun Energy Systems

Sample ID: S2965

Date of Issue: 07/10/2013



TEST RESULTS

SL. No.	Test description	Observations	Requirement as per MNRE specifications 2013-2014	Remarks
		4.0 Output (circuit to LED)		
4.1	Voltage (circuit to LED)	24.02 V DC		
4.2	Current	0.40 ADC		
4.3	Power	9.60 W		
	5.0	Overall System		
5.1	Input Voltage	12.00 VDC	12.00 VDC	
5.2	Input Current	0.90 A		
5.3	Input Power	10.8 W		
5.4	Power consumption of the electronic circuit	1.20 W	-	
5.5	Efficiency	88.88 %	85 %	
5.6	Idle current	6.19 mA	<20 mA	
5.7	PCB installation	Solder free	Solder free	
5.8	Battery temperature compensation	Provided	Required	77.
5.9	Voltage drop across battery terminal to PV module terminal	0.56 V DC	< 0.6 V DC	
5.10	Temperature rise in the heat sink after 12 hours of operation	7.31 °C	<20 °C	
	6.	0 PROTECTION		
6.1	No load protection	Provided	Required	
6.2	Short circuit	Provided	Required	
	Reverse polarity	Provided	Required	
6.3	Reverse flow protection (blocking diode)	Provided	Required	
	Ва	ttery protection		
6.4	Low voltage cut off	11.07 V DC	Required	
6.5	Load reconnect	12.49 V DC	Required	
6.6	Over charge cut off	14.04 V DC	Required	
6.7	Module reconnect	12.35 V DC	Required	

J. John Charge

Total No. of pages Page No. Report No.
4 3 2778



CENTRAL POWER RESEARCH INSTITUTE ENERGY EFFICIENCY AND RENEWABLE ENERGY DIVISION

Submitted By: M/s. Focusun Energy Systems

Sample ID: S2965

Date of Issue: 07/10/2013



TEST RESULTS

SL. No.	Test description	Observations	Requirement as per MNRE specifications 2013-2014	Remarks
		6.0 Other fea	atures	
6.1	Duty cycle	Qualifies Dusk to dawn	Dusk to dawn	
6.2	Indicators	Provided	Required	
6.3	Switch and cable	Provided	Required	14
6.4	Marking on lighting system	Provided	Required	
6.5	Marking on modules	Provided	Required	
6.6	Manual	Provided	Required	
6.7	Warranty			
	(a) Module	Provided	25 years	
	(b) Street light with charge controller	Provided	5 years	
	(c) Battery	Provided	5 years	

Conclusions: It is endorsed that the LED based solar street lighting systems submitted by M/s. Focusun Energy Systems qualifies the MNRE Specification 2013-2014 and M/s. Focusun Energy System is the original manufacturer of electronics.

Test in- charge

Total No. of pages	Page No.	Report No.
4	4	2778

